

Germination Chamber

Features

- Stainless steel and aluminum construction
- Doors swing fully open on piano hinges allowing complete access to interior
- Clear polycarbonate doors
- The circular vents can be rotated from closed to open, providing infinite adjustments
- All ventilation openings are screened
- Water reservoir has automatic water level control for supply hose
- Thermostatically controlled heating element is submerged in water to provide moist heat
- Aluminum heat baffle for more even heating
- Water level sensor turns off heating element before element damage occurs
- GFCI cord end for safety
- Digital display shows temperature within the chamber
- Easy-set thermostat controls heating and optional ventilation fans
- Shelf Brackets are spaced at 5"
- Metal edged plastic shelves are removable for easy cleaning
- 8" Casters roll smoothly over doorjamb and bumps, 2 locking
- Ships fully assembled and ready to use

Options

- Optional thermostatically controlled ventilation fans
- Optional 18-gallon gravity flow water reservoir with stand, valve, and 5' hose



Optional GT18



(If VF kit is purchased with GC then it will be installed before germination chamber is shipped.)

"Designed for Greenhouses, Schools, Universities, Research facilities, Nurseries, Market growers, and Seed Companies"

The Phytotronics Germination Chamber was designed by horticulturalists for horticulturalists. It incorporates many great features some are not available anywhere else; the door gutter collects condensation and redirects it back into the chamber to avoid puddles on the floor, low water level switch protects heating element, and the optional temperature settable ventilation fans move air through the chamber.



GC12 12-Shelf Chamber

9720	6 Shelf, 24 Flat 46"H x 51"W x 27"D	\$2,197.10
9722	12 Shelf, 48 Flat 76"H x 51"W x 27"D	2,540.80
9760	Optional Vent Fan Kit	150.00
9762	18 Gallon Tank & Stand	110.00